

RESPONSE TO RESTRICTION REQUIREMENT  
Serial No. 10/684,054  
Page 2 of 8

In the Claims

1. (Original) A substrate heater assembly for supporting a substrate of a predetermined standardized diameter during processing, comprising:
  - a body having an upper surface and a lower surface;
  - a heating element embedded within the body;
  - a substrate support surface formed in the upper surface of the body and defining a portion of a substrate receiving pocket; and
  - an annular wall oriented perpendicular to the upper surface and having a length of at least one half a thickness of the substrate, the wall bounding an outer perimeter of the substrate receiving pocket and having a diameter less than about 0.5 mm greater than the predetermined substrate diameter.
2. (Currently Amended) The assembly of claim 1 further comprising:
  - a ring disposed in the substrate receiving pocket, wherein the wall is at least a portion of an inner diameter of the ring.
3. (Original) The assembly of claim 2, wherein the ring further comprises:
  - a bevel flaring outward from the wall of the ring.
4. (Original) The assembly of claim 3, wherein the bevel is a continuous lip extending beyond the upper surface and circumscribing the wall.
5. (Withdrawn) The assembly of claim 3, wherein the bevel further comprises:
  - a plurality of discreet crowns extending beyond the upper surface and circumscribing the wall.

BEST AVAILABLE COPY

RESPONSE TO RESTRICTION REQUIREMENT  
Serial No. 10/684,054  
Page 3 of 8

6. (Original) The assembly of claim 3, wherein the ring further comprises:  
an annular flange radially outward of the wall.
7. (Withdrawn) The assembly of claim 6, wherein the flange further comprises:  
a plurality of slots formed therein.
8. (Original) The assembly of claim 2, wherein the annular ring is formed from a ceramic material.
9. (Original) The assembly of claim 2, wherein the annular ring further comprises:  
a height of about 0.7 to 7 mm; and  
a ratio of the height to a width of the annular ring between about 0.05:1 and 0.5:1.
10. (Original) The assembly of claim 3, wherein the bevel tapers outward and upward at an angle of about 10 to 40 degrees.
11. (Original) The assembly of claim 4, wherein the lip further comprises:  
a height of about 0.5 to 5 mm;  
a ratio of the height to a width of the lip between about 0.3:1 and 3:1; and  
an inner portion tapered outward and upward at an angle of about 10 to 40 degrees.
12. (Withdrawn) The assembly of claim 5, wherein at least one of the plurality of discreet crowns further comprises:  
a height of about 0.5 to 5mm;

RESPONSE TO RESTRICTION REQUIREMENT  
Serial No. 10/684,054  
Page 4 of 8

a ratio of the height to a width of the crown between about 0.3:1 and 3:1;  
and  
an inner portion tapered outward and upward at an angle of about 10 to 40 degrees.

13. (Original) The assembly of claim 1 wherein the heater member is formed from a ceramic material.

14. (Currently Amended) The assembly of claim 1, wherein the wall ~~[[is]]~~ couples the upper surface to the substrate support surface of the body.

15. (Original) The assembly of claim 14, wherein the body further comprises:  
a bevel flaring outward from the wall of the body.

16. (Original) The assembly of claim 15, wherein the bevel is a continuous lip extending beyond the upper surface and circumscribing the wall.

17. (Withdrawn) The assembly of claim 15, wherein the bevel further comprises:  
a plurality of discreet crowns extending beyond the upper surface and circumscribing the wall.

18. (Original) The assembly of claim 15, wherein the bevel tapers outward and upward at an angle of about 10 to 40 degrees.

19. (Original) The assembly of claim 16, wherein the lip further comprises:  
a height of about 0.5 to 5 mm;  
a ratio of the height to a width of the lip between about 0.3:1 and 3:1; and  
an inner portion tapered outward and upward at an angle of about 10 to 40 degrees.

RESPONSE TO RESTRICTION REQUIREMENT  
Serial No. 10/684,054  
Page 5 of 8

20. (Withdrawn) The assembly of claim 17, wherein at least one of the plurality of discreet crowns further comprises:

a height of about 0.5 to 5mm;

a ratio of the height to a width of the crown between about 0.3:1 and 3:1;

and

an inner portion tapered outward and upward at an angle of about 10 to 40 degrees.

21. (Original) An apparatus for processing a substrate of a predetermined standardized diameter, comprising:

a chemical vapor deposition chamber having a ceramic substrate heater assembly disposed therein, wherein the heater assembly comprises:

a body having an upper surface and a lower surface;

a heating element embedded within the body;

a substrate support surface formed in the upper surface of the body and defining a portion of a substrate receiving pocket; and

an annular wall oriented perpendicular to the upper surface and having a length of at least one half a thickness of the substrate, the wall bounding an outer perimeter of the substrate receiving pocket and having a diameter less than about 0.5 mm greater than the predetermined substrate diameter.

22. (Currently Amended) An apparatus for processing a substrate of a predetermined standardized diameter, comprising:

a chemical vapor deposition chamber having a ceramic substrate heater assembly disposed therein, wherein the heater assembly comprises:

a body having an upper surface and a lower surface;

a heating element embedded within the body;

a substrate support surface formed in the upper surface of the body and defining a portion of a substrate receiving pocket;

RESPONSE TO RESTRICTION REQUIREMENT  
Serial No. 10/684,054  
Page 6 of 8

an annular wall coupled between the substrate support surface and the upper surface, the wall having a length of at least one half a thickness of the substrate and a diameter less than about 0.5 mm greater than the predetermined substrate diameter; and

~~a plurality of crowns~~ a continuous lip protruding from the upper surface and circumscribing the wall, ~~each of the crowns~~ continuous lip having an inner portion joined with the bevel.

23. (Currently Amended) The assembly of claim 22, wherein ~~at least one of the plurality of discrete crowns~~ the continuous lip further comprises:

a height of about 0.5 to 5mm;

a ratio of the height to a width of the ~~crown~~ lip between about 0.3:1 and 3:1; and

~~an orientation of the inner portion~~ tapered outward and upward at an angle of about 10 to 40 degrees.

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**